

VTR-1000

Evaluation and Product Development Platform

User Guide

SOC is disclosing this user manual (the "Documentation") to you solely for use in the development of designs to operate with SOC hardware devices. You may not reproduce, distribute, republish, download, display, post, or transmit the Documentation in any form or by any means including, but not limited to, electronic, mechanical, photocopying, recording, or otherwise, without the prior written consent of SOC. SOC expressly disclaims any liability arising out of your use of the Documentation. SOC reserves the right, at its sole discretion, to change the Documentation without notice at any time. SOC assumes no obligation to correct any errors contained in the Documentation, or to advise you of any corrections or updates. SOC expressly disclaims any liability in connection with technical support or assistance that may be provided to you in connection with the Information.

THE DOCUMENTATION IS DISCLOSED TO YOU "AS-IS" WITH NO WARRANTY OF ANY KIND. SOC MAKES NO OTHER WARRANTIES, WHETHER EXPRESSED, IMPLIED, OR STATUTORY, REGARDING THE DOCUMENTATION, INCLUDING ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NONINFRINGEMENT OF THIRD-PARTY RIGHTS. IN NO EVENT WILL SOC BE LIABLE FOR ANY CONSEQUENTIAL, INDIRECT, EXEMPLARY, SPECIAL, OR INCIDENTAL DAMAGES, INCLUDING ANY LOSS OF DATA OR LOST PROFITS, ARISING FROM YOUR USE OF THE DOCUMENTATION.

© 2008-2014 SOC, Inc. All rights reserved.

SOC, the SOC logo, the Brand Window, and other designated brands included herein are trademarks of SOC, Inc.

Table of Contents

<i>Preface</i>	4
<i>1. Overview</i>	5
<i>2. Uses of the VTR-1000</i>	9
2.1 For Evaluating the SOC MPEG Codec Modules	
2.2 For Product Development	
2.3 For Product Development based on the SOC G-SoM	
2.4 As a video/audio over IP device	
<i>3. Detailed Descriptions</i>	11
3.1 FPGA Selection	
3.2 DDR3 RAM	
3.3 HDMI Transmitter	
3.4 HDMI Receiver	
3.5 3G/HD SDI Transmitter	
3.6 3G/HD SDI Receiver	
3.7 Gigabit Ethernet	
3.8 Mini USB	
3.9 Serial Flash Memory	
<i>4. Ordering Information</i>	14

Preface

About This User Guide

This User Guide describes the features and operations of the SOC VTR-1000 Evaluation and Product Development Platform. Details on the I/O interfaces and the corresponding components are provided.

Related Documents

- H.264 Encoder Datasheet
- H.264 Decoder Datasheet
- MPEG2 Encoder Datasheet
- MPEG2 Decoder Datasheet
- MPEG2-to-H.264 Transcoder Datasheet
- H.264-to-MPEG2 Transcoder Datasheet
- Product Brief for SOC MPEG Codec Modules
- Datasheet for SOC MPEG Codec Modules

VTR-1000 Evaluation and Product Development Platform

1. Overview

The SOC VTR-1000 Evaluation and FPGA Development Platform is designed for four major functions:

1. As an evaluation board for the SOC MPEG codec modules and IP Cores (encoders, decoders, and transcoders).
2. As a product development platform for systems that use the SOC MPEG codec modules or IP cores.
3. As a development board for product development based on the SOC Generic System-on-Module (G-SoM) Modules.
4. As an OEM product of H.264/MPEG2 video/audio over IP or via WiFi transponder.

A unique feature of the VTR-1000 is that it has two DDR3 connectors that are used to connect to the SOC MPEG codec modules (the SOC MPEG Codec module series) and the SOC G-SoM modules (FPGA/DSP-SoM-1000 series). Users can use the VTR-1000 to evaluate the SOC MPEG codec modules or IP cores, and then use the same board for product development.

The VTR-1000 has its own FPGA chip (the Xilinx Spartan-6 LX45T) which controls the I/Os and can be combined with the FPGA on the G-SoM module. This allows for the product development of multiple FPGA based systems.

The VTR-1000 with an encoder and decoder module is a fully functional H.264 (or MPEG-2) video/audio over the Internet (IP) transponder that can be packaged into an enclosure box for end-user uses. It provides HDMI input, HDMI output, 3G/HD SDI input, 3G/HD SDI output, and an Ethernet port with the UDP/RTP/IP compatibilities. The VTR-1000 also has a WiFi port that can connect to a WiFi module for wireless video transmission. Contact SOC sales@soctechnologies.com for details.

The VTR-1000 Evaluation Board and FPGA Development Platform is shown in Figure 1 (top view) and Figure 2 (bottom view) with the SOC Codec modules plugged on to the DDR3 connectors. A block diagram of the system is provided in Figure 3.

VTR-1000 Top View




Fig.1 VTR-1000 Top View




Fig. 2 VTR-1000 bottom View




Fig.3 VTR-1000 Block Diagram

Key Features

- Xilinx LX45T FPGA
- 2 GB DDR3 RAM
- Two DDR3 connectors for SOC MPEG Codec Modules or SOC SOM-1000 modules
- HDMI input
- HDMI output
- 3G/HD-SDI input
- 3G/HD-SDI output
- Ethernet
- Two WiFi connectors for WiFi modules
- Mini USB
- Two Pmod Connectors
- Push buttons
- LEDs
- Power rails for SOC MPEG Codec Modules or SOC SOM-1000 modules

2. Uses the VTR-1000

2.1 For Evaluating the SOC MPEG Codec Modules

The VTR-1000 is preloaded with firmware for evaluating the SOC MPEG codec modules. It is a plug-and-play system that allows the user to insert the desired module (encoder, decoder, or transcoder), and connect the I/O devices to start the evaluation.

For encoder evaluation, the input video source is sent to the VTR-1000 via the HDMI or SDI input port; the encoded stream is sent to the computer through the Ethernet port. Users can decode the encoded streams by using standard software decoders.

For decoder evaluation, the compressed streams are sent to the VTR-1000 through the Ethernet. The software for sending the streams is provided as part of the VTR-1000 package. The decoded video and audio streams are sent to the HDMI or SDI output port for display.

For simultaneous evaluation of the encoder and the decoder, the input video stream is sent to the VTR-1000 via the HDMI or SDI input port. The input video stream is encoded by the encoder, and then sent to the decoder for decoding. The decoded video stream is sent to the HDMI or SDI output port for display. The end-to-end latency of encoding and decoding can be measured by observing the time difference of the input video stream versus the output video stream.

Two VTR-1000 boards can be used to test the video transmission over WiFi, with one VTR-1000 acting as transmitter and the second acting as receiver.

For transcoder evaluation, both the input stream and transcoded stream are sent through the Ethernet port.

Detailed instructions for evaluating the SOC encoders and decoders using the VTR-1000 are provided in “Instruction Sheet of Using the VTR-1000 to Evaluate SOC Codec Modules and IP cores”.

2.2 For Product Development

The VTR-1000 is a versatile platform for product development, based on the SOC MPEG codec modules (or IP cores).

SOC provides (under licensing agreement) a “netlist” IP cores for all the I/O ports, including the network stack for the VTR-1000, so that the users can drop them into their own designs without having to implement the I/O modules.

Design templates of the I/O drivers and the network stack IP cores are available for licensing. These can greatly speed up the development process.

The schematics design of the VTR-1000 is available to the customers who have purchased the board, which provides the details information for using the board and a reference for user product design.

Users can also purchase the design files (e.g. Gerber file) from SOC, which can be used as a reference for the user PCB once the product is developed. Contact SOC sales (sales@soctechnologies.com) for details.

2.3 For Product Development based on the SOC G-SoM

The SOC SoM modules can also be used as generic System on Module (SoM) platform for user designs. The VTR-1000 is equipped with one FPGA, one DSP, and with the required memory blocks. This allows users to download their own firmware/software to configure the module according to their specific design. Once configured, the module can be used as SoM module for user applications. This accelerates product development and saves costs. Refer to the datasheet of the G-SoM-1000 for further details.

2.4 As an H.264 (or MPEG-2) Video over WiFi OEM Product

The VTR-1000, with a H.264 (MPEG-2) encoder and a decoder module, is a ready to use H.264 (or MPEG-2) video/audio over WiFi transponder which is offered as an OEM product by SOC. Contact SCO sales@soctechnologies.com for information.

3. Detailed Descriptions

Table-1 lists the components on the VT-1000 that are important to the users. Refer to the schematics of the VTR-1000 for the circuit design and the auxiliary components. The schematics of the VTR-1000 is included with the board on delivery.

The following Sections describe the components listed in Table-1. Refer to the datasheets of the components for further details.

Table-1 Major components on the VTR-1000

Item	Reference in Schematics	Part Name	Description	Manufacturer
1	U6	XC6SLX45-2FGG484C	FPGA, Spartan-6, LX150/LX100/LX75/LX45	Xilinx
2	U9	MT41J128M16JT-125:K	DDR3 SDRAM 2GBit	Micron Technology Inc
3	U4	ADV7511KSTZ-P	HDMI Transmitter	Analog Devices Inc
4	U1	ADV7611BSWZ-P	HDMI receiver	Analog Devices Inc
5	U19	LMH0384	3 Gbps HD/SD SDI Cable Equalizer	TI
6	U18	LMH0303	3 Gbps HD/SD SDI Cable Driver	TI
7	U5	88E1111_BAB1C000	Gigabit Ethernet Transceiver, 10/100/1000	Marvell
8	U8	N25Q128A13EF740F	128Mb, Serial Flash Memory	MICRON
9	Y3	ASFL1-27.000MHZ-L-T	OSCILLATOR 27.000 MHZ 3.3V	ABRACON
10	Y4	ASFLMB-100.000MHZ-XY-T	OSCILLATOR MEMS 100.000 MHZ	ABRACON
11	Y1	ABM3-28.6363MHZ-B2-T	CRYSTAL 28.6363MHZ 18PF	Abracon Corporation
12	Y2	ABM8-25.000MHZ-B2-T	CRYSTAL 25.000MHZ 18PF	Abracon Corporation
13	J2	MM80-204B1	CONN 204POS DDR3 SDRAM SODIMM	JAE Electronics
14	U7	DS28E01P-100+	1Kb PROTECTED 1-WIRE EEPROM	MAXIM

3.1 FPGA Selection

The FPGA on the VTR-1000 is Xilinx LX45T. Refer to the schematics of the VTR-1000 and Data Sheet of the FPGAs for further details.

3.2 DDR3 RAM

The VTR-1000 is equipped with an off-chip DDR3 RAM of 2Gbit, which can be used for systems that require off-the-chip memory blocks. Refer to the datasheet of MT41J128M16JT-125 for the specifications and the allocations of this memory block.

The SOC VTR-1000 Reference Design provides an example of using this DDR3 RAM.

3.3 HDMI Transmitter

The HDMI Transmitter is the ADV7511KSTZ-P by Analog Devices. Refer to the Datasheet of ADV7511KSTZ-P for details.

SOC provides the configuration file for ADV7511KSTZ-P which is a part of the I/O driver package. For evaluations, the ADV7511KSTZ-P is preconfigured for plug-and-play.

The SOC VTR-1000 Reference Design provides an example of using ADV7511KSTZ-P.

3.4 HDMI Receiver

The HDMI Receiver is the ADV7611BSWZ-P by Analog Devices. Refer to the Datasheet of ADV7611BSWZ-P for details.

SOC provides the configuration file for ADV7611BSWZ-P which is a part of the I/O driver package. For evaluations, the ADV7611BSWZ-P is preconfigured for plug-and-play.

The SOC VTR-1000 Reference Design provides an example of using ADV7611BSWZ-P.

3.5 3Gbps HD/SD SID Cable Driver

The VTR-1000 provides a 3 Gbps HD/SD SDI output through a cable driver, the TI LMH0303, and an SDI IP core inside the FPGA, Xilinx Spartan-6 LX45T. The SDI IP core is pre-loaded onto the VTR-1000, when the VTR-1000 is used for evaluating the SOC codec modules or IP cores. For product development purposes, the SDI IP core is available for licensing.

3.6 Gigabit Ethernet

The Ethernet PHY is the 88E1111_BAB1C000 by Marvel. It can be used for 10Mbps/100Mbps/1000Mbps. The configuration file is included in the I/O package. An Ethernet MAC core is a part of the Ethernet/UDP/IP network stack which can be licensed. For evaluations, the networks stack is preloaded to allow a plug-and-play system.

The SOC VTR-1000 Reference Design provides an example of using M88E1111_BAB1C000.

3.7 Serial Flash Memory

The serial flash memory, N25Q128A13EF740F, is used to store the firmware of the FPGA. For evaluation, the I/O drivers and the Ethernet/UDP/IP network stack are pre-stored in the N25Q128A13EF740F. When the FMC-MCM-1000 is booted, the firmware stored in the N25Q128A13EF740F will configure the FPGA and make the board a plug-and-play device to facilitate the evaluations of the SOC MPEG codec modules.

After the evaluation, users can store their own firmware into the N25Q128A13EF740F for product development. For product development purposes, the I/O driver and the Ethernet/UDP/IP network stack IP core in “netlist” format are available for licensing. The method of downloading the firmware into the N25Q128A13EF740F is detailed in Appendix-C.

4. Ordering Information

The FMC-MCM-1000 can be ordered from SOC directly or through the distributors of SOC. Refer to the SOC web site, www.soctechnologies.com , for distributor locations and contact information.

SOC contacts:

E-mail: sale@soctechnologies.com

Telephone: 1-519-880-8609

Revision History

The following table shows the revision history for this document.

Date	Version	Revision
1/10/2013	SOC initial Release	
20/11/2014	Version 1.00	Rev. 1
02/12/2014	Version 1.10	Rev. 2
09/07/2015	Version 1.20	Rev. 3